

RADIATOR FLUSH

Spanjaard Radiator Flush is a concentrated blend of inorganic salts with dissolving and chelating properties which effectively aid the removal of accumulated rust, scale and sludge inside radiators.

APPLICATIONS

- Safe in aluminium engine blocks and cylinder heads and is not harmful to hoses or gaskets.

DIRECTIONS FOR USE

1. Drain off 375ml of water from radiator.
2. Add the contents of the bottle to the radiator.
3. Run the engine until water is warm.
4. Run at idle for a further 15 minutes.
5. Drain radiator and flush with water hose.
6. Refill with clean water.
7. In severe cases, repeat treatment.

PROPERTIES

Colour:	Red Liquid
Features:	• Specific gravity: 1.096

PACKAGING

375 ml	bottle
5 L	plastic container
20 L	plastic container



Revision: 080324

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

