

“T” CUTTING FLUID/SPRAY & “T” CUTTING COMPOUND

Spanjaard ‘T’ Cutting Fluid is an extreme pressure metal working fluid, used undiluted in a variety of machining operations on any metal and most plastics. Available also in an aerosol (“T” Cutting Spray). **Spanjaard ‘T’ Cutting Compound** is used to cut threads on piping and tubing.

APPLICATIONS

- **Spanjaard ‘T’ Cutting Fluid/Spray** is used for difficult machining, reaming, tapping, drilling, broaching and thread cutting operations.
- Prolongs lifespan of a tool by reducing friction at low speeds and preventing welding at high speeds.

DIRECTIONS FOR USE

1. **Spanjaard ‘T’ Cutting Fluid** is applied using the dripper bottle or as a spray from the aerosol.
2. **Spanjaard ‘T’ Cutting Compound** is applied to threads by finger or brush.

PROPERTIES

T’CUTTING COMPOUND

Colour:	Caramel/beige
Features:	<ul style="list-style-type: none"> • Appearance: Paste • Work penetration: 265—295

“T” CUTTING FLUID/SPRAY

Colour:	Brown
Features:	<ul style="list-style-type: none"> • Appearance: liquid • Specific gravity: 1.28—1.30

PACKAGING

Spanjaard ‘T’ Cutting Fluid

300ml Aerosol
375ml, 5L, 20L and 210L

Spanjaard ‘T’ Cutting Compound

500g, 5kg, 15kg.



Revision: 090224

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

